

NetPoint NP6-DP-2FT (NP62)





Parabolic Antenna High Performance



NetPoint's NP62-DP-2FT super high performance dish antenna is designed to work with very high performance in both licensed and unlicensed bands with excellent gain. The NP62-DP-2FT model has dual polarization and an N-female connector, as well as exceptional VSRW performance in the 5.9 to 7.2 GHz operating band. The antenna comes pre-assembled and ready to install, as well as an integrated radome for high performance and reliable operation in the most demanding conditions. This 2-foot parabolic antenna can be used for PTP backhaul, CPE and public safety applications.



FEATURES AND BENEFITS

- Gain of up to 30 dBi with low VSWR and high port isolation across the entire 5.9 -7.2 GHz band
- One antenna that covers 6 and 7 Ghz
- Reduced interference with >39 dB minimum front to back
- Simplifies installation on site and guarantees "factory-tested" guality
- Connector type N Female
- Pigtails of N to RPSMA included in the box for free!!!

ELECTRIC SPECIFICATIONS

Antenna type Directional parabolic reflector 5.9 - 7.2 Ghz Frecuency Connector type Female N Gain (dBi) 29, 30 28. 5.9GHz, 6.8GHz and 7.2GHz VSWR HPOL <2.0 Beamwidth VPOL 4.2° Beamwidth HPOL 4.0° Impedance (Ohms) 50 Radius F/B (dB) >39 Polarization Dual slant 45° or 90°

MECHANICAL SPECIFICATIONS

Wind max survival speed (MPH) 124.2 miles with Radome Azimuth adjustment Elevation adjustment (°) Mounting Pipe Diameter, Min Mounting Pipe Diameter, Max Operating temperature (C°) Connector type

+/- 60 degrees +/- 15 degrees 1 inch - 25.4mm 2.95 inch 75.00mm -49 to +140 F° | -45 to +60 C° Dual N-Female with pigtails for **RP-SMA** 2ft - 600 mm

Lenght of Pig tail


SHIPPING INFORMATION

Type of package Gross weight (Kg) Dimensions, L x W x H Shipping volume


Cardboard 14.3lb - 6.5kg 28.34 x 28.24 x 11.41in 72cm x 72cm x 29cm 5.29 cu ft | 0.14 cu m



RADIATION PATTERN



Vertical



Horizontal

TECHNICAL DRAWING

